

可变压力式调压器

Variable Pressure Regulator



此类调压器是一种可根据客户的实际需要压力而随意调整的调压器。有电动式和手轮式两种式样。

This product enables the supply pressure to be adjusted freely close at hand. Two types, one equipped with a control motor and another with a handle, are available.



规格 Specifications

型号 Model	进口压力 Inlet pressure	出口压力设定范围 Outlet pressure range	进口连接 Inlet connection	出口连接 Outlet connection	放散阀 Safety valve	流量范围(Air) Flow rate range		变压方式 Adjusting method	
						标准 ~ 最大 *1 Standard Maximum			
I-72-1	0.13~1.56MPa	0.01~0.07MPa	POL 阳 (male)	Rc1/2	无 Without	3 ~ 5 Nm ³ /h(air)		手动 Manual type	
I-72-2	0.17~1.56MPa	0.01~0.16MPa				3 ~ 5 Nm ³ /h(air)			
I-72-3	0.40~1.56MPa	0.01~0.35MPa				3 ~ 5 Nm ³ /h(air)			
CM-100-H1	0.1~1.56MPa	20~300kPa	JIS20K 15A 法兰 JIS 20K15A flange	JIS10K 15A 法兰 JIS 10K 15A flange		20 ~ 30 Nm ³ /h(air)			
GMF-70-H1			JIS20K 20A 法兰 JIS 20K20A flange	JIS10K 20A 法兰 JIS 10K20A flange		45 ~ 70 Nm ³ /h(air)			
CM-100-H2	0.1~0.4MPa	2~40kPa	JIS20K 15A 法兰 JIS 20K15A flange	JIS10K 15A 法兰 JIS 10K 15A flange		20 ~ 30 Nm ³ /h(air)			
GMF-70-H2			JIS20K 20A 法兰 JIS 20K20A flange	JIS10K 20A 法兰 JIS 10K20A flange		45 ~ 70 Nm ³ /h(air)			
GMF-70-M	0.05~0.35MPa	2~40kPa	JIS20K 20A 法兰 JIS 20K20A flange	JIS10K 20A 法兰 JIS 10K20A flange		25 ~ 70 Nm ³ /h(air)			电动 With motor
GMF-100-M	0.05~0.35MPa	2~40kPa	JIS20K 25A 法兰 JIS 20K25A flange	JIS10K 25A 法兰 JIS 10K25A flange		50 ~ 100 Nm ³ /h(air)			
G-32A-M	0.04~0.1MPa	4~15kPa	JIS10K 25A 法兰 JIS 10K25A flange	1 1/2b 油拧 1 1/2a Union	50 ~ 100 Nm ³ /h(air) ^{*2}				
G-36C-M			JIS10K 40A 法兰 JIS 10K40A flange	2b 油拧 2a Union	100 ~ 200 Nm ³ /h(air) ^{*2}				
GL-500-M			JIS10K 50A 法兰 JIS 10K50A flange	JIS10K 80A 法兰 JIS 10K80A flange	250 ~ 500 Nm ³ /h(air) ^{*2}				

*1 在最大流量使用情况下,需要0.1MPa以上压差。

In the case of using the items in maximum flow rate, the differential pressure will be needed at least 0.1MPa.

*2 在最大流量使用情况下,需要0.07MPa以上压差。

In the case of using the items in maximum flow rate, the differential pressure will be needed at least 0.07MPa.

控制电动机 Control motor	行程 stroke	时钟频率 Timing	电源 Power	功率消耗 Consumption	微调电阻 Potentionmeter
	90度 90°	50Hz/72sec 60Hz/60sec	AC-100V	20W	135Ω

PC 接口

PC socket

此接口是一种POL 螺口(外丝)和锥度丝口的连接件。
PC socket is the connection adapter between POL(Male) and Taper screw.



规格 Specifications

型号 Model	进出口接口 Connection
PC-106	POL (阴female) × Rc1/4
PC-112	POL (阴female) × Rc3/8
PC-115	POL (阴female) × Rc1/2
PC-206	POL (阴female) × R1/4
PC-212	POL (阴female) × R3/8
PC-215	POL (阴female) × R1/2